

NSWCDD/TR-92/527

AD-A285 087
11

ANTITACTICAL BALLISTIC MISSILE GLOBAL EFFECTIVENESS MODEL (AGEM) INTERCEPT ALGORITHM

BY J. A. LAWTON C. A. BYRUM
STRATEGIC AND SPACE SYSTEMS DEPARTMENT

JULY 1994

Approved for public release; distribution is unlimited.

DTIC
ELECTE
SEP 23, 1994



NAVAL SURFACE WARFARE CENTER

DAHLGREN DIVISION

DAHLGREN, VIRGINIA 22448-5100

DTIC QUALITY INSPECTED 3

94 9 80 1 23

SRP
94-31063
11

**ANTITACTICAL BALLISTIC MISSILE
GLOBAL EFFECTIVENESS MODEL (AGEM)
INTERCEPT ALGORITHM**

**BY J. A. LAWTON C. A. BYRUM
STRATEGIC AND SPACE SYSTEMS DEPARTMENT**

JULY 1994

Approved for public release, distribution is unlimited

**NAVAL SURFACE WARFARE CENTER
DAHLGREN DIVISION
Dahlgren, Virginia 22448-5100**

DDTC QUOTE 1 UNCLASSIFIED 3

FOREWORD

The intercept algorithm presented in this report is central to the Antitactical Ballistic Missile Global Effectiveness Model (AGEM) and is intended to be a robust and operationally flexible solution method. This report discusses the derivation of the exact derivatives required to iteratively solve operationally constrained Lambert problems. Examples of the implemented algorithm's convergence characteristics are also presented.

This report has been reviewed by Ted Sims, Head, Space Sciences Branch, and J. L. Sloop, Head, Space and Surface Systems Division.

Approved by:

R. L. Schmidt

R. L. SCHMIDT, Head
Strategic and Space Systems Department

Attention: For	
1	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>
3	<input type="checkbox"/>
4	<input type="checkbox"/>
5	<input type="checkbox"/>
6	<input type="checkbox"/>
7	<input type="checkbox"/>
8	<input type="checkbox"/>
9	<input type="checkbox"/>
10	<input type="checkbox"/>
11	<input type="checkbox"/>
12	<input type="checkbox"/>
13	<input type="checkbox"/>
14	<input type="checkbox"/>
15	<input type="checkbox"/>
16	<input type="checkbox"/>
17	<input type="checkbox"/>
18	<input type="checkbox"/>
19	<input type="checkbox"/>
20	<input type="checkbox"/>
21	<input type="checkbox"/>
22	<input type="checkbox"/>
23	<input type="checkbox"/>
24	<input type="checkbox"/>
25	<input type="checkbox"/>
26	<input type="checkbox"/>
27	<input type="checkbox"/>
28	<input type="checkbox"/>
29	<input type="checkbox"/>
30	<input type="checkbox"/>
31	<input type="checkbox"/>
32	<input type="checkbox"/>
33	<input type="checkbox"/>
34	<input type="checkbox"/>
35	<input type="checkbox"/>
36	<input type="checkbox"/>
37	<input type="checkbox"/>
38	<input type="checkbox"/>
39	<input type="checkbox"/>
40	<input type="checkbox"/>
41	<input type="checkbox"/>
42	<input type="checkbox"/>
43	<input type="checkbox"/>
44	<input type="checkbox"/>
45	<input type="checkbox"/>
46	<input type="checkbox"/>
47	<input type="checkbox"/>
48	<input type="checkbox"/>
49	<input type="checkbox"/>
50	<input type="checkbox"/>
51	<input type="checkbox"/>
52	<input type="checkbox"/>
53	<input type="checkbox"/>
54	<input type="checkbox"/>
55	<input type="checkbox"/>
56	<input type="checkbox"/>
57	<input type="checkbox"/>
58	<input type="checkbox"/>
59	<input type="checkbox"/>
60	<input type="checkbox"/>
61	<input type="checkbox"/>
62	<input type="checkbox"/>
63	<input type="checkbox"/>
64	<input type="checkbox"/>
65	<input type="checkbox"/>
66	<input type="checkbox"/>
67	<input type="checkbox"/>
68	<input type="checkbox"/>
69	<input type="checkbox"/>
70	<input type="checkbox"/>
71	<input type="checkbox"/>
72	<input type="checkbox"/>
73	<input type="checkbox"/>
74	<input type="checkbox"/>
75	<input type="checkbox"/>
76	<input type="checkbox"/>
77	<input type="checkbox"/>
78	<input type="checkbox"/>
79	<input type="checkbox"/>
80	<input type="checkbox"/>
81	<input type="checkbox"/>
82	<input type="checkbox"/>
83	<input type="checkbox"/>
84	<input type="checkbox"/>
85	<input type="checkbox"/>
86	<input type="checkbox"/>
87	<input type="checkbox"/>
88	<input type="checkbox"/>
89	<input type="checkbox"/>
90	<input type="checkbox"/>
91	<input type="checkbox"/>
92	<input type="checkbox"/>
93	<input type="checkbox"/>
94	<input type="checkbox"/>
95	<input type="checkbox"/>
96	<input type="checkbox"/>
97	<input type="checkbox"/>
98	<input type="checkbox"/>
99	<input type="checkbox"/>
100	<input type="checkbox"/>

Dist

A-1

ABSTRACT

This report discusses general solutions to the spaceflight intercept problem between moving source and target vehicles, under the constraint that only one limited thrust burn is permitted. This one burn is approximated as an instantaneous change in velocity, Δv . Given first is a discussion of the solution space, aided by Lambert's theorem. Generally, two solutions (and sometimes more) to the posed intercept problem exist for a given launch time. Although previous solution techniques in the literature concentrate on finding the minimum time solution, both solutions are significant from an operational and a theoretical standpoint. Next, exact derivatives for two different operational requirements are derived, which facilitate finding all solutions to the intercept problem. Finally, example numerical problems solved by the Antitactical Ballistic Missile Global Effectiveness Model (AGEM) are presented to demonstrate the solution process for both operational requirements.

CONTENTS

	<u>Page</u>
INTRODUCTION	1
SOLUTION SPACE	2
SIMPLE ITERATION SCHEME FOR CASE 1	5
CASE 1 DERIVATIVE	6
CASE 2 PROCEDURES	11
EXAMPLES AND COMPARISONS ..	13
CONCLUSIONS	23
REFERENCES	23
DISTRIBUTION	(1)

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	TYPICAL Δv VERSUS TOF CURVE	3
2	TYPICAL LAUNCH-TIME/TOF LEVEL CURVE	3
3	TYPICAL LAUNCH-TIME/INTERCEPT-TIME LEVEL CURVE	4
4	EXAMPLE SOLUTION SPACE	14
5	EXAMPLE CONSTRAINTS	15

CONTENTS (Continued)

<u>Figure</u>		<u>Page</u>
6	EXAMPLE 1 CONVERGENCE	20
7	EXAMPLE 2 CONVERGENCE	21
8	EXAMPLE 7 CONVERGENCE	21

TABLES

<u>Table</u>		<u>Page</u>
1	EXAMPLE SUMMARY: FLIGHT TIME LIMITS CONVERGED	15
2	EXAMPLE 1: NEW ALGORITHM—CASE 1	16
3	EXAMPLE 2: NEW ALGORITHM—CASE 1	16
4	EXAMPLE 3: OLD ALGORITHM—CASE 1	17
5	EXAMPLE 4: NEW ALGORITHM—CASE 1	18
6	EXAMPLE 5: NEW ALGORITHM—CASE 1	18
7	EXAMPLE 6: NEW ALGORITHM—CASE 1	19
8	EXAMPLE 7: NEW ALGORITHM—CASE 1	19
9	EXAMPLE 8: NEW ALGORITHM—CASE 2	20

INTRODUCTION

The spaceflight intercept problem discussed herein is to find the intercept trajectory from a source vehicle in orbit (or on the Earth) to a target vehicle in orbit (or on the Earth), with fixed thrusting capabilities. Many authors have discussed various problems related to this intercept problem. The classical Lambert problem¹ (viz., find the trajectory that flies between two fixed positions in a specified time-of-flight (TOF)) is intimately related, but the problem considered here involves moving source and target vehicles, not fixed positions. The minimum fuel intercept problem² does consider moving source and target trajectories, allowing the number of burns and the amount of fuel to be variable. In an operational environment, however, the size and type of engine, amount of fuel, etc., are fixed, so there is a requirement to find intercept solutions with these fixed thrusting capabilities. This is especially important for solid propellant engines, which generally burn only once. This report presents results when the thruster allows only one burn with a fixed characteristic velocity. This burn is approximated as an instantaneous change in velocity, Δv .

Parks, et al.,³ describe a hybrid technique for solving the one-burn constrained characteristic velocity intercept problem. The technique first uses a simple maximum range check to reduce the search space of launch/intercept time pairs. Then, to find specific solutions, an iterative technique on the interceptor TOF is applied to obtain the Δv , which achieves intercept when added to the source vehicle velocity. Extensive numerical experience with this algorithm has shown that it always finds the minimum time solution if the initial guess on TOF is sufficiently small (probably due to the small flight path angle assumption), but it never converges to the maximum time solution. The next section shows that both solutions are significant from an operational and a theoretical standpoint. So the algorithm of Parks, et al., is very fast if minimum time solutions are desired, but it is not robust for finding general solutions. Cochran and Davy⁴ also developed an iterative algorithm which obtains an initial guess from an approximate solution to find the constrained one-burn minimum time solution to the intercept problem.

This report discusses the fixed impulse intercept problem from a broader viewpoint than that of finding minimum time solutions. Tools are developed to facilitate finding all solutions to the intercept problem, with a view to satisfying a variety of operational requirements. If a specified characteristic velocity must be satisfied, then specific solutions meeting operational requirements can be found with these tools. If a maximum characteristic velocity is given, and the engine can be throttled to obtain lower energy burns, then a range of solutions can be obtained.

SOLUTION SPACE

To understand what type of analysis techniques are required to find solutions to the intercept problem, the shape of the solution space must be understood. Figure 1 contains a typical plot of $|\Delta v|$ versus TOF for orbiting source and target vehicles. It is obtained by solving Lambert's problem for numerous values of the TOF. As the TOF approaches zero, the required $|\Delta v|$ approaches infinity. Δv_g is the given characteristic velocity of the source. The points where the horizontal Δv_g line crosses the $|\Delta v|$ curve correspond to solutions to the posed problem. The first solution (minimum value of TOF) corresponds to the depressed trajectory solution (low initial flight path angle, low apogee, and short TOF), while the second solution is the lofted trajectory (high initial flight path angle, etc.). This is analogous to the two solutions obtainable for the ballistic missile problem,⁵ where trajectories are sought between two fixed positions at the same altitude, with the velocity magnitude at the source point being a fixed value. In that case, it can be shown analytically that for velocities less than escape velocity and ranges less than the maximum range, two solutions (a lofted and a depressed solution) always exist. For velocities of at least escape velocity, only one solution exists. At maximum range and velocities less than escape velocity, again only one solution exists. Extending this result to more general transfer problems, Lambert's theorem¹ states that flight between two fixed positions of different altitudes can be converted into an equivalent problem with equal altitudes, so that the above results are true between any fixed positions. It is therefore not a surprise that this property still generally holds even when considering flight between two moving vehicles.

Any TOF between these two solution times (depicted in Figure 1) is possible if the engine can be throttled or energy dissipation maneuvers are adopted. The subsequent damped oscillations of the $|\Delta v|$ curve correspond to $|\Delta v|$ requirements for second and later revs of the target trajectory. If the horizontal line at Δv_g crosses the $|\Delta v|$ curve more than twice, it generally means that long flight times corresponding to later revs of the target are achievable with the given Δv_g characteristic velocity. The resulting interceptor trajectories are very lofted, "hanging" until the next pass of the target. These hanging interceptor trajectories approach, but never reach, a parabolic trajectory, so the upper bound for these damped oscillations is the $|\Delta v|$ that yields escape velocity. Usually, however, later rev intercepts are not of practical importance, so the first two solutions are the only ones of interest.

If various launch times are considered, a series of plots like those shown in Figure 1 can be put together to consider the effect of launch time as well as TOF. Figure 2 shows a resultant level curve in launch-time/TOF space for the Δv_g level curve. That is, launch-time/TOF pairs on the curve are solutions. Any launch-time/TOF pair on the interior of the region bounded by the curve requires less $|\Delta v|$ than Δv_g . Since the intercept time is the launch time plus the TOF, Figure 2 is easily converted into a launch-time/intercept-time level curve depicted in Figure 3.



FIGURE 1. TYPICAL Δv VERSUS TOF CURVE

FIGURE 2. TYPICAL LAUNCH-TIME/TOF LEVEL CURVE




FIGURE 3. TYPICAL LAUNCH-TIME/INTERCEPT-TIME LEVEL CURVE

The information in Figure 3 can be used to discuss solutions to various operational requirements. First, suppose knowledge of all possible launch times is required to schedule maneuvers, taking into account external operational requirements. For a simplistic example, control facilities may need to coordinate independent maneuvers, so the union and intersection of the launch times for various vehicles may be required. In this case, all times between $t_{L,1}$ and $t_{L,2}$ in Figure 3 yield achievable intercept. Call the need to schedule launch times a Case 1 operational requirement. On the other hand, there may be a need to schedule intercept times. Again, for a simplistic example, monitoring facilities may require intercepts of various vehicles to occur at separate times, so the knowledge of all achievable intercept times between $t_{I,1}$ and $t_{I,2}$ in Figure 3 permits the coordination of intercept times. Call the need to schedule intercept times a Case 2 operational requirement. Notice that different techniques are required to solve Case 1 problems than are required for Case 2 problems, since in general $t_{L,1}$ does not correspond to $t_{I,1}$ (that is, $t_{L,1}$ is not the launch time that achieves intercept at $t_{I,1}$); this is also true for $t_{L,2}$ and $t_{I,2}$. Knowledge of the intervals $[t_{L,1}, t_{L,2}]$ and $[t_{I,1}, t_{I,2}]$ alone are not sufficient; solutions for specific launch times or specific intercept times are also required.

SIMPLE ITERATION SCHEME FOR CASE 1

The double iteration scheme proposed in this report for Case 1 operational requirements is similar to that described by Parks, et al.³ Since the launch time is fixed in Case 1, the position of the launcher is fixed in the attempt to find the trajectory that intercepts the moving target with the prescribed magnitude of the velocity change vector, Δv . First, a guess of the TOF of the intercept trajectory, τ , is made, which fixes the time of intercept, and hence the position of the target at intercept. With the launch and target positions known, and with the given τ , finding the trajectory between those positions that traverses the path between them in time τ is merely a Lambert problem. This Lambert problem can be solved by a variety of iteration schemes; one of the more robust algorithms is given by Battin.¹ The Lambert iteration is the inner loop of the double iteration scheme.

The solution of Lambert's problem results in knowledge of the initial velocity vector of the intercept trajectory; the difference between this velocity and that of the launcher trajectory yields the Δv at launch. $|\Delta v|$ is then the characteristic velocity of the interceptor required to perform this maneuver. The specified fixed characteristic velocity of the interceptor vehicle in question (Δv_g), however, is in general different from $|\Delta v|$. So, the outer loop of this iteration scheme must adjust the TOF, τ , in order to drive the error $\delta v \triangleq |\Delta v| - \Delta v_g$ to zero. Parks, et al.,³ proposed one scheme of updating τ based on an approximate derivative. In this report, a better method for updating τ is presented, which uses an exact derivative and is more robust over a wider domain of the problem.

Specifically, the exact derivative of δv with respect to the TOF, $\frac{d\delta v}{d\tau}$, for both Case 1 and Case 2 problems, is presented. Knowledge of this derivative allows a classical Newton's method to be performed in order to iterate on τ

$$\tau_{n+1} = \tau_n - \frac{\delta v(\tau_n)}{\left(\frac{d\delta v}{d\tau}\right)_{\tau_n}} \quad (1)$$

The derivation of $\frac{d\delta v}{d\tau}$ is given in the next section. Furthermore, knowledge of this derivative facilitates finding regions where solutions to $\delta v = 0$ exist and whether they exist for the particular problem at hand.

To illustrate this, refer again to Figure 1, which shows a typical plot of $|\Delta v|$ as a function of τ for a case where both the source and target are vehicles in low Earth orbit. The horizontal line corresponds to the hardware prescribed Δv_g ; where the curve crosses this horizontal line corresponds to solutions to the posed intercept problem. If the first possible intercept is desired, then the depressed trajectory is chosen.

The value of $\frac{d\delta v}{dt}$ at the solution is negative for a depressed trajectory and positive for a lofted trajectory. The value of τ where $\frac{d\delta v}{dt} = 0$ corresponds to the minimum energy trajectory, which separates the depressed from the lofted trajectory. These observations lead to the following method for finding both depressed and lofted trajectories.

First, solve for $\frac{d\delta v}{dt} = 0$ to find the minimum achievable $|\Delta v|$, denoted Δv_{min} , occurring at TOF τ_{min} . If $\Delta v_{min} > \Delta v_g$, then no intercept is possible at this launch time. On the other hand, if intercept is achievable, then the depressed solution occurs at some $\tau_{dep} \in (0, \tau_{min})$, so that the solution is bounded. A Newton iteration, Equation 1, generally finds τ_{dep} swiftly when the initial guess $\tau_0 \in (0, \tau_{min})$. It has been found advantageous to augment the Newton iteration with checks to assure that convergence is occurring. A switch to some safe bracketing algorithm such as bisection is recommended in the rare event when the Newton iteration is not converging. To find the lofted trajectory, Newton's method can be used with an initial guess $\tau_0 > \tau_{min}$. Again, checks should

be implemented to ensure convergence. A test to assure that $\frac{d\delta v}{dt} = 0$ will also help guarantee that the convergence is occurring in the correct region.

If the minimum possible TOF is the one that is always desired, then starting with a short TOF as the initial guess and iterating with Newton's method until con-

vergence usually works very well. If $\frac{d\delta v}{dt}$ becomes positive in the iteration process, then the minimum energy solution has been passed, and it can be assumed that the minimum $|\Delta v|$ is greater than Δv_g . That is, no solution is possible. If a solution is possible, the iteration usually finds it rapidly.

CASE 1 DERIVATIVE

Since $|\Delta v| = \sqrt{\Delta v \cdot \Delta v}$, the desired derivative of the error in Δv with respect to TOF is

$$\frac{d\delta v}{dt} = \frac{d}{dt} (|\Delta v| - \Delta v_g) = \frac{d}{dt} \sqrt{\Delta v \cdot \Delta v} = \frac{\Delta v}{|\Delta v|} \cdot \frac{d\Delta v}{dt} \quad (2)$$

Furthermore, $\frac{d\Delta v}{dt} = \frac{dv_o}{dt}$ (where v_o denotes the initial velocity of the intercept trajectory), because the velocity of the source vehicle is fixed with respect to τ . So

$$\frac{d\delta v}{dt} = \frac{\Delta v}{|\Delta v|} \cdot \frac{dv_o}{dt} \quad (3)$$

This means that the derivative $\frac{dv_o}{dt}$ is required. For notational convenience, let subscript "1" denote quantities related to the source trajectory, let subscript "2" denote quantities related to the target trajectory, and let subscripts "o" and "f" denote initial and final quantities of the intercept trajectory. Then, as long as r_1 and v_o are linearly independent (i.e., the interceptor trajectory is not rectilinear), the final intercept trajectory position can be written as a linear combination of these two vectors

$$r_2 = f r_1 + g v_o \quad (4)$$

The scale factors are the so-called "f and g expressions," which are well-known functions of the intercept geometry.⁶ Specifically

$$f = 1 + \frac{r_2}{p} (\cos \Delta v - 1) \quad (5)$$

and

$$g = \frac{r_1 r_2 \sin \Delta v}{\sqrt{\mu p}} \quad (6)$$

where r_1 and r_2 are magnitudes of r_1 and r_2 , Δv is the angle between r_1 and r_2 , p is the semi-latus rectum of the intercept orbit, and μ is the gravitational parameter. Solving Equation 4 for v_o yields

$$v_o = \frac{r_2 - f r_1}{g} \quad (7)$$

This gives the derivative

$$\frac{dv_o}{dt} = \frac{\left(v_2 - \frac{df}{dt} r_1\right)g - (r_2 - f r_1) \frac{dg}{dt}}{g^2} \quad (8)$$

In turn, the derivatives $\frac{df}{dt}$ and

$\frac{dg}{dt}$ must be determined. Differentiating Equations 5 and 6 yields

$$\frac{df}{dt} = \left(\frac{\dot{r}_1 p - r_2 \frac{dp}{dt}}{p^2} \right) (\cos \Delta v - 1) - \frac{r_2}{p} \sin \Delta v \frac{d\Delta v}{dt} \quad (9)$$

and

$$\frac{dg}{dt} = \left(\frac{r_1 r_2 \sin \Delta v + r_1 r_2 \cos \Delta v \frac{d\Delta v}{dt}}{\sqrt{\mu p}} \right) - \frac{r_1 r_2 \sin \Delta v}{2 \sqrt{\mu p^3}} \frac{dp}{dt} \quad (10)$$

$$\text{Since } \cos \Delta v = \frac{\mathbf{r}_1 \cdot \mathbf{r}_2}{r_1 r_2}$$

$$\frac{d\Delta v}{dt} = \frac{\dot{r}_2 (\mathbf{r}_1 \cdot \mathbf{r}_2) - r_2 (\mathbf{r}_1 \cdot \dot{\mathbf{r}}_2)}{r_1 r_2^2 \sin \Delta v} \quad (11)$$

Now the only undetermined derivative is $\frac{dp}{dt}$. To find this derivative, a relationship between the semi-latus rectum, "p," of the intercept orbit and the TOF must be found. The TOF equation as a function of orbital parameters, which in turn are implicit functions of "p," gives the desired relationship. For elliptical trajectories, Bate, et al.,⁶ give the TOF for the intercept trajectory

$$\tau = g + \sqrt{\frac{a^3}{\mu}} (\Delta E - \sin \Delta E) \quad (12)$$

where a is the semimajor axis and ΔE is the change in eccentric anomaly of the intercept trajectory. Each of the three variables on the right side of the equation is a function of "p," so that implicit differentiation of both sides with respect to τ will cause $\frac{dp}{dt}$

to appear on the right side of the equation. $\frac{dp}{dt}$ can then be solved for algebraically.

To this end, first cast g , a , and ΔE in terms of geometric parameters and p (and previously defined functions of these quantities)⁶

$$g = \frac{r_1 r_2 \sin \Delta v}{\sqrt{\mu p}} \quad (13)$$

$$a = \frac{m k p}{(2m - l^2) p^2 + 2 k l p - k^2} \quad (14)$$

and

$$\cos^2\left(\frac{\Delta E}{2}\right) = \frac{(k - l p)^2}{2 m p^2} \quad (15)$$

Here the auxiliary geometry functions k , l , and m are

$$k = r_1 r_2 (1 - \cos \Delta v) \quad (16)$$

$$l = r_1 + r_2 \quad (17)$$

and

$$m = r_1 r_2 (1 + \cos \Delta v) \quad (18)$$

Hence, Equation 12 can be written functionally as

$$\tau = F\left(g\left[r_2(\tau), \Delta v(\tau), p(\tau)\right], a\left[k(\tau), l(\tau), m(\tau), p(\tau)\right], \Delta E\left[k(\tau), l(\tau), m(\tau), p(\tau)\right]\right) \quad (19)$$

Implicitly differentiating Equation 19

$$\begin{aligned} \frac{d\tau}{d\tau} = 1 &= \frac{\partial F}{\partial g} \left(\frac{\partial g}{\partial r_2} r_2 + \frac{\partial g}{\partial \Delta v} \frac{d\Delta v}{d\tau} + \frac{\partial g}{\partial p} \frac{dp}{d\tau} \right) \\ &+ \frac{\partial F}{\partial a} \left(\frac{\partial a}{\partial k} \frac{dk}{d\tau} + \frac{\partial a}{\partial l} \frac{dl}{d\tau} + \frac{\partial a}{\partial m} \frac{dm}{d\tau} + \frac{\partial a}{\partial p} \frac{dp}{d\tau} \right) \\ &+ \frac{\partial F}{\partial \Delta E} \left(\frac{\partial \Delta E}{\partial k} \frac{dk}{d\tau} + \frac{\partial \Delta E}{\partial l} \frac{dl}{d\tau} + \frac{\partial \Delta E}{\partial m} \frac{dm}{d\tau} + \frac{\partial \Delta E}{\partial p} \frac{dp}{d\tau} \right) \end{aligned} \quad (20)$$

Solving Equation 20 for $\frac{dp}{d\tau}$

$$\begin{aligned} \frac{dp}{d\tau} &= D \cdot \left\{ 1 - \frac{\partial F}{\partial g} \left(\frac{\partial g}{\partial r_2} r_2 + \frac{\partial g}{\partial \Delta v} \frac{d\Delta v}{d\tau} \right) - \frac{\partial F}{\partial a} \left(\frac{\partial a}{\partial k} \frac{dk}{d\tau} + \frac{\partial a}{\partial l} \frac{dl}{d\tau} + \frac{\partial a}{\partial m} \frac{dm}{d\tau} \right) \right. \\ &\quad \left. - \frac{\partial F}{\partial \Delta E} \left(\frac{\partial \Delta E}{\partial k} \frac{dk}{d\tau} + \frac{\partial \Delta E}{\partial l} \frac{dl}{d\tau} + \frac{\partial \Delta E}{\partial m} \frac{dm}{d\tau} \right) \right\} \end{aligned} \quad (21)$$

where

$$D = \frac{1}{\frac{\partial F}{\partial g} \frac{\partial g}{\partial p} + \frac{\partial F}{\partial a} \frac{\partial a}{\partial p} + \frac{\partial F}{\partial \Delta E} \frac{\partial \Delta E}{\partial p}} \quad (22)$$

Each of the derivatives in Equations 21 and 22 are easily derived by straightforward differentiation of formulas given above.

Now Equation 21 can be used in Equations 9 and 10, together with Equation 11, to compute Equation 8. Equation 8, in turn, is used in Equation 3 to obtain the desired derivative to be used in Newton's method, Equation 1.

If the current intercept trajectory is hyperbolic, then $\frac{d\delta v}{dt}$ must be determined with the TOF equation corresponding to hyperbolic flight⁶

$$t = g + \sqrt{\frac{-a^3}{\mu}} (\sinh \Delta F - \Delta F) \quad (23)$$

where ΔF is the hyperbolic eccentric anomaly. Let the right side of this equation be called G. Then, analogous to Equation 21, the same procedure is used to find

$$\begin{aligned} \frac{dp}{dt} = D_h \cdot \left\{ 1 - \frac{\partial G}{\partial g} \left(\frac{\partial g}{\partial r_2} \dot{r}_2 + \frac{\partial g}{\partial \Delta v} \frac{d\Delta v}{dt} \right) - \left(\frac{\partial G}{\partial a} + \frac{\partial G}{\partial \Delta F} \frac{\partial \Delta F}{\partial a} \right) \left(\frac{\partial a}{\partial k} \frac{dk}{dt} + \frac{\partial a}{\partial l} \frac{dl}{dt} + \frac{\partial a}{\partial m} \frac{dm}{dt} \right) \right. \\ \left. - \frac{\partial G}{\partial \Delta F} \frac{\partial \Delta F}{\partial f} \left(\frac{\partial f}{\partial r_2} \dot{r}_2 + \frac{\partial f}{\partial \Delta v} \frac{d\Delta v}{dt} \right) \right\} \end{aligned} \quad (24)$$

where

$$D_h = \frac{1}{\frac{\partial G}{\partial g} \frac{\partial g}{\partial p} + \frac{\partial G}{\partial a} \frac{\partial a}{\partial p} + \frac{\partial G}{\partial \Delta F} \left(\frac{\partial \Delta F}{\partial a} \frac{\partial a}{\partial p} + \frac{\partial \Delta F}{\partial f} \frac{\partial f}{\partial p} \right)} \quad (25)$$

The only new function here, other than G, is that relating ΔF to intercept geometry parameters (and its derivatives)⁶

$$\cosh \Delta F = 1 - \frac{r_1}{a} (1 - f) \quad (26)$$

CASE 2 PROCEDURES

For Case 2 operational requirements (find the launch times to intercept at a fixed intercept time), a slightly modified iteration scheme must be employed. In this case, since the intercept time (and hence the intercept position) is fixed, a variable TOF means that the launch location is moving as a function of τ . For example,

$\frac{dr}{d\tau} = -\frac{dr}{dt} = -v$, if r is the position of the source vehicle, since an increase in τ means that the time of launch is decreasing. The most straightforward method of handling this problem would be to start the above process again, but now allowing r_1 to vary as a function of τ instead of r_2 .

An alternative method, which makes use of the symmetry of Keplerian orbits, takes advantage of most of the Case 1 derivatives. Consider a trajectory from a starting point to a terminal point. If a trajectory is flown from the terminal point with the negative of the terminal velocity, the same trajectory will be traversed in the opposite direction, reaching the starting point in the same TOF with a velocity equal to the negative of the starting velocity. So, the problem of finding launch times to intercept at a fixed intercept time can be recast into a problem where the launch orbit becomes the target orbit and the target orbit becomes the launch orbit. The only adjustment that must be made is that all velocities involved become the negative of those in the real problem. For the rest of this section, the notation reflects the recast problem (for example, r_2 in the recast problem is really the launch position in the starting problem, v_2 is the negative of the starting interceptor velocity, etc.).

The only difference between the recast problem and the Case 1 problem is that the prescribed velocity, Δv_g , must now be matched at the terminal point instead of the starting point. Using the notation from Case 1 for the recast problem, the requirement is, given that

$$\Delta v_f = v_f - v_2 \quad (27)$$

$$\delta v_f \triangleq |\Delta v_f| - \Delta v_g = 0 \quad (28)$$

The requisite derivative for Newton's method of finding the zero of the δv_f function is

$$\frac{d\delta v_f}{d\tau} = \frac{d}{d\tau} (|\Delta v_f| - \Delta v_g) = \frac{d}{d\tau} \sqrt{\Delta v_f \cdot \Delta v_f} = \frac{\Delta v_f}{|\Delta v_f|} \cdot \frac{d\Delta v_f}{d\tau} \quad (29)$$

In turn

$$\frac{d\Delta v_f}{d\tau} = \frac{dv_f}{d\tau} - \frac{dv_2}{d\tau} \quad (30)$$

But since the change in v_2 in TOF is the same as the change in v_2 in time, (i.e.,

$\frac{dv_2}{dt} = \frac{dv_2}{dt}$), its derivative is just the gravitational acceleration. So

$$\frac{d\Delta v_f}{dt} = \frac{dv_f}{dt} + \frac{\mu r_2}{|r_2|^3} \quad (31)$$

To find the derivative of v_f , write it as⁶

$$v_f = \dot{f} r_1 + \dot{g} v_o \quad (32)$$

Then

$$\frac{dv_f}{dt} = \frac{df}{dt} r_1 + \frac{dg}{dt} v_o + g \frac{dv_o}{dt} \quad (33)$$

Note that $\frac{dv_o}{dt}$ has already been determined for Case 1 problems, so the remaining derivatives to be determined are the derivatives of \dot{f} and \dot{g} . The equation for \dot{g} is⁶

$$\dot{g} = 1 - \frac{r_1}{p} (1 - \cos \Delta v) \quad (34)$$

so that

$$\frac{dg}{dt} = -\frac{r_1}{p^2} (1 - \cos \Delta v) \frac{dp}{dt} - \frac{r_1}{p} \sin \Delta v \frac{d\Delta v}{dt} \quad (35)$$

Everything on the right side of the equation has already been determined in the previous section. As for \dot{f} , the identity

$$1 = f g - f g \quad (36)$$

can be differentiated to yield

$$\frac{df}{dt} = \frac{1}{g} \left(f \frac{dg}{dt} + \dot{g} \frac{df}{dt} - f \frac{dg}{dt} \right) \quad (37)$$

Again, all other derivatives have already been determined in the previous section.

EXAMPLES AND COMPARISONS

Various examples of the intercept algorithm used in the Antitactical Ballistic Missile Global Effectiveness Model (AGEM) follow. This model has been used in various configurations to simulate orbiter-to-orbiter, ground-to-orbiter, and ground-to-ground engagements for Strategic Defense Initiative (SDI), antisatellite (ASAT) and antitactical ballistic missile (ATBM) scenarios. The examples that follow are exclusively orbiter-to-orbiter intercepts.

For the orbiting satellite that will launch the interceptors in this series of examples, the initial inertial position and velocity vectors are

$$\mathbf{r}_s = \begin{bmatrix} 7015.9485 \\ 0.0 \\ 0.0 \end{bmatrix} \text{ km}$$

$$\mathbf{v}_s = \begin{bmatrix} 0.0 \\ 7.5496259965 \\ 0.0 \end{bmatrix} \text{ km/sec}$$

The starting inertial position and velocity vectors of the orbiting target are

$$\mathbf{r}_t = \begin{bmatrix} 5740.3215 \\ 3189.0675 \\ -3189.0675 \end{bmatrix} \text{ km}$$

$$\mathbf{v}_t = \begin{bmatrix} 2.82181264515 \\ 1.5676736918 \\ 6.64693645322 \end{bmatrix} \text{ km/sec}$$

Figure 4 shows the $|\Delta \mathbf{v}|$ and τ solution space for interceptors launched at time 0.0 (corresponding to the initial \mathbf{r}_s). The minimum velocity intercept solution is

$$|\Delta \mathbf{v}| = 0.649912 \text{ km/sec}$$

$$\mathbf{v}_o = 7.989828 \text{ km/sec}$$

$$\tau = 462.3349 \text{ sec}$$

In each of the eight examples presented, the required intercept impulse is $\Delta \mathbf{v}_g = 3.95268 \text{ km/sec}$, and the flight time is constrained between 0 and 3000 sec. The 3000-sec limit has been arbitrarily imposed to keep engagement solutions inside a single-orbit revolution of the target. Algorithm iteration convergence tolerances are 0.00001 km/sec for velocity and 0.001 sec for flight time. For these parameters, there are two possible intercept trajectories; one depressed with a flight time of 338.9 sec and one lofted with a flight time of 705.4 sec.




FIGURE 4. EXAMPLE SOLUTION SPACE

Table 1 summarizes the examples and shows the type of trajectory to which the algorithm converged and the number of iterations required. Figure 5 shows the constraints imposed on each example. For each of the example convergence data tables, n refers to the iteration number and n_c refers to the number of iterations required to achieve convergence of the Lambert iteration (inner loop). The flight time and impulse for each step are also shown. The last row in the table presents the last significant iteration trial. The actual final pass through the algorithm yields identical results, to the accuracy presented. In each table, the initial flight time guess ($n = 1$) is the first row.

Examples 1 and 2 demonstrate the classic use of the algorithm where either the lofted (maximum flight time) or depressed (minimum flight time) trajectory is acceptable. Example 1 uses an initial flight time guess well below the depressed solution, while Example 2 uses an initial guess well above the lofted solution. Convergence data for Example 1 are shown in Table 2. Example 2 data are listed in Table 3.

Example 3, which uses the algorithm specified by Parks, et al.,³ is presented for convergence characteristics comparison and for completeness. Table 4 contains data for this example.

TABLE 1. EXAMPLE SUMMARY. FLIGHT TIME LIMITS AND CONVERGENCE RESULTS

Ex.	Eq. Type	Case	Min (sec)	Guess (sec)	Max (sec)	Trajectory Type	n
1	New	1	1.0	10.0	3000.0	Depressed	12
2	New	1	1.0	1500.5	3000.0	Depressed	11
3	Parks	1	1.0	10.0	3000.0	Depressed	20
4	New	1	1.0	3.0	462.3	Depressed	12
5	New	1	1.0	231.7	462.3	Depressed	10
6	New	1	462.3	464.3	3000.0	Lofted	10
7	New	1	463.3	1731.7	3000.0	Lofted	9
8	New	2	1.0	10.0	3000.0	Depressed	16




FIGURE 5. EXAMPLE CONSTRAINTS

TABLE 2. EXAMPLE 1: NEW ALGORITHM - CASE 1
($1 \leq \tau \leq 3000$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	12	10.0000	459.318
2	10	19.7153	228.333
3	9	38.3218	112.882
4	8	72.4360	55.2278
5	7	129.734	26.5586
6	6	210.451	12.5754
7	5	290.762	6.30517
8	4	332.161	4.24263
9	5	338.804	3.95835
10	5	338.939	3.95273
11	12	338.940	3.95266
12	8	338.940	3.95268

TABLE 3. EXAMPLE 2: NEW ALGORITHM - CASE 1
($1 \leq \tau \leq 3000$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	5	1500.50	8.71621
2	6	196.303	14.2024
3	5	279.510	6.96989
4	5	328.640	4.39801
5	7	338.626	3.9658.
6	9	338.940	3.95271
7	15	338.940	3.95269
8	5	338.941	3.95270
9	5	338.941	3.95265
10	12	338.940	3.95266
11	8	338.940	3.95268

TABLE 4. EXAMPLE 3. PARKS, ET AL. - CASE 1
($1 \leq t \leq 3000$)

n	n_i	t (sec)	$ \Delta v $ (km/sec)
1	12	10.0000	459.518
2	10	19.8032	227.278
3	9	38.8237	111.301
4	8	74.5508	53.3887
5	7	137.058	24.6163
6	6	229.529	10.6950
7	5	318.122	4.88246
8	4	341.971	3.82679
9	7	338.225	3.98275
10	5	339.099	3.94600
11	4	338.904	3.95418
12	8	338.948	3.95234
13	5	338.938	3.95279
14	7	338.941	3.95266
15	7	338.940	3.95267
16	5	338.940	3.95271
17	5	338.940	3.95262
18	5	338.939	3.95272
19	5	338.940	3.95266
20	7	338.940	3.95268

Examples 4 and 5 have been forced to converge on the depressed trajectory by virtue of the flight time limits used. Example 4 has specified an unreasonably small initial flight time guess, while Example 5 has specified an initial guess very near the solution. Example 4 data are listed in Table 5, and Example 5 data are given in Table 6.

Examples 6 and 7 have been forced to find the lofted solution because of the minimum flight time requirements. The initial guess in Example 6 is lower than the expected lofted trajectory solution, while that in Example 7 is above the expected lofted trajectory solution. Data for these examples are listed in Tables 7 and 8, respectively. Notice that in both these examples the algorithm makes use of the implemented safe bracketing method to bring the flight time into the neighborhood of the known solution.

TABLE 5. EXAMPLE 4: NEW ALGORITHM - CASE 1
($1 \leq \tau \leq 462.3$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	14	3.00000	1552.95
2	12	4.97440	775.044
3	11	11.8480	386.204
4	10	23.2963	191.790
5	9	45.0426	94.6228
6	8	84.2637	46.1264
7	7	147.999	22.0711
8	6	232.049	10.4694
9	5	305.637	5.50047
10	4	338.90	4.09023
11	5	338.909	3.95398
12	14	338.940	3.95268

TABLE 6. EXAMPLE 5: NEW ALGORITHM - CASE 1
($1 \leq \tau \leq 462.3$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	6	231.668	10.5033
2	5	305.398	5.51278
3	5	335.644	4.09221
4	6	338.908	3.95404
5	5	338.940	3.95262
6	5	338.939	3.95272
7	5	338.940	3.95274
8	6	338.941	3.95264
9	12	338.940	3.95266
10	8	338.940	3.95268

TABLE 7. EXAMPLE 6: NEW ALGORITHM - CASE 1
($462.3 \leq \tau \leq 3000$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	3	464.335	0.65162
2	4	2415.38	11.5062
3	3	462.335 +	0.64991
4	5	1731.17*	9.49904
5	5	1308.22*	7.95633
6	6	1096.75*	6.93482
7	3	551.024	1.89556
8	5	679.003	3.65531
9	5	704.564	3.94370
10	5	705.385	3.95268

NOTE: The following indicate that the algorithm's flight time guess is outside the externally imposed flight time limits:

+ = reset Tff guess to Tff min.

* = using bisection to reset Tff guess

TABLE 8. EXAMPLE 7: NEW ALGORITHM - CASE 1
($463.3 \leq \tau \leq 3000$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	5	1731.67	9.50062
2	3	463.335 +	0.65034
3	5	1731.67*	9.50062
4	5	1308.89*	7.95919
5	6	1097.50*	6.93892
6	3	550.488	1.88695
7	5	678.856	3.65359
8	5	704.555	3.94360
9	5	705.385	3.95268

NOTE: The following indicate that the algorithm's flight time guess is outside the externally imposed flight time limits:

+ = reset Tff guess to Tff min.

* = using bisection to reset Tff guess

Example 8 demonstrates the "backward" (Case 2) solution of the minimum flight time intercept. In this example, the interceptor is "launched" from r_t propagated forward to 338 sec (the "forward" depressed trajectory impact time). The algorithm is required to find a solution that has an "impact" closing velocity equal to the required velocity. In this "backward" intercept, flight time is effectively negative, so that "impact" at r_s is before "launch" from r_t . Algorithm convergence data are presented in Table 9.

TABLE 9. EXAMPLE 8: NEW ALGORITHM - CASE 2
($1 \leq i \leq 3000$)

n	n_i	τ (sec)	$ \Delta v $ (km/sec)
1	9	10.0000	131.124
2	8	19.6991	66.5680
3	7	38.2312	34.3066
4	6	72.0749	18.2096
5	5	128.610	10.22591
6	5	207.990	6.35474
7	5	278.909	4.62525
8	6	331.125	4.04192
9	6	338.754	3.95473
10	5	338.937	3.95274
11	7	338.942	3.95266
12	16	338.941	3.95265
13	5	338.937	3.95275
14	5	338.943	3.95264
15	5	338.939	3.95270
16	16	338.941	3.95268

Though the algorithm presented in this report is substantially more complex than that presented by Parks, et al.,³ this new algorithm converges to a solution more quickly. Examination of the number of iterations required for Examples 1 and 3 in Table 1 demonstrates that the increase in complexity (lines of code) is offset by more rapid convergence characteristics.

Examples 1, 4, and 6 demonstrate how judicious specification of intercept flight time bounds can be used to choose between maximum and minimum intercept flight time solutions. In Example 1, the time limits indicate that there is no real preference of trajectory shape. The bounds set in Examples 4 and 6 force the algorithm to find only the depressed or lofted trajectory shapes, respectively. However, knowledge of the solution space minimums (Figure 4) is required.

Comparison of Examples 1 and 2 shows that the algorithm converged to the depressed trajectory in both examples. This is due to the slope of the curve past the neighborhood of the lofted solution. This value tends to correct the succeeding flight time iteration to a value near or below the depressed solution, which is then converged to. This is a manifestation of the geometry of this example and of the initial flight time guess. Figures 6 and 7 are graphical representations of the convergence behavior for Examples 1 and 2, respectively.

Examples 6 and 7 show the necessity of implementing an auxiliary convergence method, such as a bisection method. In both these examples, the value of the slope at the initial flight time guess causes the next guess by the standard iteration method to fall outside the allowed limits. At this point, as shown in Figure 8 (Example 7), a bisection method can be used to force subsequent flight time iterations into the neighborhood of the solution, at which point the presented equations take over and converge.

In summary, the algorithm presented in this report is robust. In the presence of stressing engagement geometries, Newton's iteration requires augmentation using some safe bracketing method to guarantee convergence within the specified flight time bounds.




FIGURE 6. EXAMPLE 1 CONVERGENCE





FIGURE 7. EXAMPLE 2 CONVERGENCE



CONCLUSIONS

The new algorithm for solving single-impulse intercept problems is a significant improvement over existing methods for three reasons. First, it has the intrinsic ability to find either or both of the solutions that exist in the typical intercept scenario, as opposed to finding only the minimum time solutions as extant methods do. Second, the iteration scheme converges rapidly. Third, the algorithm can solve for either set launch times or set intercept times depending on whether launch times or intercept times need to be scheduled. These attributes combine to produce an algorithm that is both flexible in its ability to handle a wide variety of intercept problems and robust in its capacity to rapidly converge to appropriate solutions. It has proven valuable in diverse space and naval defense analyses.

REFERENCES

1. Battin, R. H., "Solving Lambert's Problem," *An Introduction to the Mathematics and Methods of Astrodynamics*, American Institute of Aeronautics and Astronautics, New York, 1987, pp. 295-342.
2. Lawton, J. A., *Fuel-Optimal Space-Flight Transfer Solutions Through a Redundant Adjoint Variable Transformation*, Ph.D. Dissertation, Dept. of Aerospace and Ocean Engineering, Virginia Tech, Apr 1991.
3. Parks, A. D., Lawton, J. A., and Bell, D. B., *Simple Hybrid Search Technique for Finding Conic Solutions to the Intercept Problem*, J. Guidance, Vol. 12, Sep - Oct 1989, pp. 754-766.
4. Cochran, J. E., Jr., and Davy, A. H., *Constrained Initial Guidance Algorithm*, J. Guidance, Vol. 13, Mar - Apr 1990, pp. 193-197.
5. Bate, R. R., Mueller, D. D., and White, J. E., *Ballistic Missile Trajectories*, Fundamental of Astrodynamics, Dover, New York, 1971, pp. 277-320.
6. Bate, R. R., Mueller, D. D., and White, J. E., *Orbit Determination From Two Positions and Time*, Fundamental of Astrodynamics, Dover, New York, 1971, pp. 227-275.

DISTRIBUTION

	Copies		Copies
DOD ACTIVITIES (CONUS)		ATTN CODE 37	1
ATTN SEA 06	1	COMMANDER	
SEA 06R	1	NAVAL AIR WARFARE CENTER	
COMMANDER		CHINA LAKE CA 93555-6001	
NAVAL SEA SYSTEMS COMMAND		DEFENSE TECHNICAL INFORMATION	
2531 JEFFERSON DAVIS HWY		CENTER	
ARLINGTON VA 22242-5760		CAMERON STATION	
ATTN CODE 12	1	ALEXANDRIA VA 22304-6145	12
COMMANDER		NON-DOD ACTIVITIES	
OFFICE OF CHIEF OF NAVAL RESEARCH		ATTN F H LUTZE	1
APPLIED RESEARCH AND TECHNOLOGY		DEPARTMENT OF AEROSPACE AND	
DIRECTORATE		OCEAN ENGINEERING	
800 N QUINCY ST		VIRGINIA TECH	
ARLINGTON VA 22217-5000		BLACKSBURG VA 24061	
ATTN CODE 30	1	ATTN LUIGI PERINI	1
OFFICE OF CHIEF OF NAVAL RESEARCH		APPLIED PHYSICS LABORATORY	
OFFICE FOR APPLIED TECHNOLOGY		JOHNS HOPKINS UNIVERSITY	
800 N QUINCY ST		JOHNS HOPKINS RD	
ARLINGTON VA 22217-5000		LAUREL MD 20723-6099	
ATTN CODE 005	1	ATTN GIFT & EXCHANGE DIVISION	4
COMMANDER		LIBRARY OF CONGRESS	
SPACE AND NAVAL WARFARE		WASHINGTON DC 20540	
SYSTEMS COMMAND		INTERNAL	
2451 CRYSTAL GATEWAY BLDG 5		E231	3
WASHINGTON DC 20362-5222		E282 (GRAY)	1
ATTN T SOLER	1	G205	1
NGS/NOS/NOAA N/CG		G21	1
6001 EXECUTIVE BLVD		G23	1
ROCKVILLE MD 20852		K13	20
ATTN CODE 8000	1	K14	5
NAVAL CENTER FOR SPACE		K105	1
TECHNOLOGY		K106	1
COMMANDING OFFICER		K107	1
NAVAL RESEARCH LABORATORY		K40	1
4555 OVERLOOK DR SW		K44	1
WASHINGTON DC 20375-5320		N74 (GIDEP)	1

REPORT DOCUMENTATION PAGE

Form Approved
OMB No 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1994		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE Antitactical Ballistic Missile Global Effectiveness Model (AGEM) Intercept Algorithm				5. FUNDING NUMBERS	
6. AUTHOR(S) J. A. Lawton C. A. Byrum					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center, Dahlgren, Division (Code K13) 17320 Dahlgren Rd. Dahlgren, VA 22448-5100				8. PERFORMING ORGANIZATION REPORT NUMBER NSWCDD/TR-92/527	
9. SPONSORING/MONITORING AGENCY NAME(S) AND				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This report discusses general solutions to the spaceflight intercept problem between moving source and target vehicles, under the constraint that only one limited thrust burn is permitted. This one burn is approximated as an instantaneous change in velocity, Δv . Given first is a discussion of the solution space, aided by Lambert's theorem. Generally, two solutions (and sometimes more) to the posed intercept problem exist for a given launch time. Although previous solution techniques in the literature concentrate on finding the minimum time solution, both solutions are significant from an operational and a theoretical standpoint. Next, exact derivatives for two different operational requirements are derived, which facilitate finding all solutions to the intercept problem. Finally, example numerical problems solved by the Antitactical Ballistic Missile Global Effectiveness Model (AGEM) are presented to demonstrate the solution process for both operational requirements.					
14. SUBJECT TERMS Antitactical Ballistic Missile Global Effectiveness Model (AGEM) Intercept Algorithm Spaceflight Intercept Lambert's Theorem				15. NUMBER OF PAGES 32	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL		

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and its title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

BLOCK 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If Known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."
DOE - See authorities.
NASA - See Handbook NHB 2200.2
NTIS - Leave blank

Block 12b. Distribution Code.

DOD - Leave blank.
DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.
NASA - Leave blank.
NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*)

Block 17.-19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of this page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited or SAR (same as report)). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.